

TECHNICAL DATA SHEET

Date of issue: 27.06.2014

Last updating:



SIRO S.r.l.

Via Meucci, 5 - Z.I. Selve
35037 Teolo - Padova
Tel. 049.990.11.22
Fax 049.990.15.36
e-mail: vendite@siropaints.com
www.siropaints.com

Name: ACCELERATOR-THINNER

Definition: additive for 2k acrylic and polyurethane systems

Code: 03.034

Category: additive

V.O.C. ready to use: 920 g/l

Product outside the uses referred to
2004/42/CE

NATURE OF THE PRODUCT

Acrylic thinner with additive inside

GENERAL USES

It can be used to accelerate all the 2k acrylic and polyurethane solvent based systems

APPLICATION METHOD

PREPARATION OF THE PRODUCT

Add the additive in the A part of the 2k system that you mean to speed up, in a percent that goes from 0.5% to 1.5% by weight maximum.

Be careful, an surplus of additive can allow the formation of pinholes on the final film of the paint (expecially when you reach an high final thickness), for this reason we suggest to start with a minimum dose and going on and on to increase the quantity as long as your experience on it will grow.

TECHNICAL DATA

PRODUCT TYPE: Transparent liquid

COLOURS: transparent

SPECIFIC WEIGHT
(ISO 2811): 0,93 kg/l. ($\pm 0,03$).

SOLIDS CONTENT: 10 % ($\pm 1\%$)

STORAGE
STABILITY: 2 year, stored in closed packs, in a cool, dry place, away from any sources of heat.