

TECHNICAL DATA SHEET

Date of issue: 11.01.2011

Last updating:



SIRO S.r.l.

Via Meucci, 5 - Z.I. Selve
35037 Teolo - Padova
Tel. 049.990.11.22
Fax 049.990.15.36
e-mail: vendite@siropaints.com
www.siropaints.com

Name: AGENT FOR GLASS

Definition: Adhesion promoter

Code: 03.029

Category: additive

V.O.C. ready to use: 490 g/l

Product outside the uses referred to
2004/42/CE

NATURE OF THE PRODUCT

Siliane based adhesion promoter.

GENERAL USES

Application on glass, stone and special metals.

APPLICATION METHOD

PREPARATION OF THE SURFACE AND THE PRODUCT

The cleaning of the application surface should be total and painstaking and it is a fundamental and necessary condition to obtain positive result of the painting cycle.

Add 2-3% by weight of the additive to the painting cycle. The percentage must be calculated on the ready-to-use product. Mix carefully and apply. The additive could be added to the painting even before hardening and dilution.

The additive is suitable for epoxy, acrylic, polyurethane and synthetic solvent based painting systems.

TECHNICAL DATA

PRODUCT TYPE: Transparent liquid

SPECIFIC WEIGHT
(ISO 2811): 0,984 g/ml

SOLIDS CONTENT: 65%±2%

STORAGE
STABILITY: Two years, stored in closed packs, in a cool, dry place, away from any sources of heat.