

TECHNICAL DATA SHEET

Date of issue: 27.06.2014

Last updating:



SIRO S.r.l.

Via Meucci, 5 - Z.I. Selve
35037 Teolo - Padova
Tel. 049.990.11.22
Fax 049.990.15.36
e-mail: vendite@siropaints.com
www.siropaints.com

Name:	ANTIGRAFFITI ADDITIVE	Category:	additive
Definition:	additive for 2k acrylic and polyurethane systems	V.O.C. ready to use:	920 g/l
Code:	03.035	Product outside the uses referred to	2004/42/CE

NATURE OF THE PRODUCT

Additive based on silicone polymer and nano-technological systems

GENERAL USES

It can be used to improve resistance to scratch, writing, and dirtiness in all the 2k acrylic and polyurethane solvent based systems

APPLICATION METHOD

PREPARATION OF THE PRODUCT

Add the additive in the A part of the 2k system in a percent that goes from 2% to 4% by weight. Be careful, an surplus of additive can give origin to undesired effects. For this reason we suggest to do some preliminary tests when you mean to go over the percentage suggested .

TECHNICAL DATA

PRODUCT TYPE:	Transparent liquid
COLOURS:	transparent
SPECIFIC WEIGHT (ISO 2811):	0,93 kg/l. ($\pm 0,03$).
SOLIDS CONTENT:	14 % ($\pm 1\%$)
STORAGE STABILITY:	2 year, stored in closed packs, in a cool, dry place, away from any sources of heat.