

TECHNICAL DATA SHEET

Date of issue: 04/11/2013

Last updating: n.1 12/01/2021



SIRO S.r.l.

Via Meucci, 5 - Z.I. Selve
35037 Teolo - Padova
Tel. 049.990.11.22
Fax 049.990.15.36
e-mail: vendite@siropaints.com
www.siropaints.com

Name:	SICCATIVE FOR SYNTHETICS	Category:	additive
Definition:	Drying agent	V.O.C. ready to use:	600 g/l
Code:	03.003	Product outside the uses referred to	2004/42/CE

NATURE OF THE PRODUCT

Mixture of metal salts of cobalt, calcium and zirconium.

GENERAL USES

It is indicated to accelerate the hardening reaction of enamels based on synthetic resins.

APPLICATION METHOD

Add a quantity of 03.003 to the enamel equal to 0.5 - 0.8% by weight, calculated on the ready-to-use product, thus including the dilution necessary for application.

PREPARATION OF THE PRODUCT

Mix the enamel thoroughly until a uniform consistency and colour are obtained, then proceed with the addition of 03.003 and continue stirring until a homogeneous mixture is obtained.

WARNINGS FOR USE

Any overdosing can cause the formation of bittiness on the surface of the enamel, which can be seen when it dries.

In the preparation of white enamels, excessive use of this additive causes purple shades that can compromise the final colour: in these cases, it is necessary to carry out preliminary verification tests.

Flammable product intended for professional use, to be used with adequate personal protection and to be stored in a dry and ventilated environment, away from sources of combustion.

Consult the Safety Data Sheet for correct handling and storage.

Do not disperse in the environment.

TECHNICAL DATA

PRODUCT TYPE:	Additive
COLOURS:	Opalescent, purplish-brown colour.
SPECIFIC WEIGHT (iso 2811):	0,93 kg/l. ($\pm 0,05$).
STORAGE STABILITY:	Two years, stored in closed packs, in a cool, dry place, away from any sources of heat.